

# FLEXIPLUMB™

## PLUMBING MADE EASY WITH THE FLEXIPLUMB RANGE

INNOVATIVE AND VERSATILE EPDM RUBBER PLUMBING CONNECTIONS  
FOR DOMESTIC AND COMMERCIAL USE  
FOR PROFESSIONAL PLUMBERS AND D.I.Y. MARKET



**SIMPLE WAYS TO SAVE MONEY  
EASY TO FIT AND DO IT YOURSELF!**

Compliant with EN 681-2 Standards  
Manufactured in EPDM, (Ethylene Propylene Diene Monomer (M Class)) Rubber

Environmental Products & Services Ltd.  
5, Shepherd's Drive, Carnbane Ind. Est.  
Newry, Co. Down, N. Ireland, BT35 6JQ  
Tel: +44 (0) 28 3083 3081  
Fax: +44 (0) 28 3083 3081  
[www.EPAS-Ltd.com](http://www.EPAS-Ltd.com)

Environmental   
Products & Services Ltd.  
[www.EPAS-Ltd.com](http://www.EPAS-Ltd.com)

## BENEFITS

- Highly flexible allowing for misalignment.
- Freedom from corrosion.
- Ideal for permanent use, emergency and temporary repairs.
- Connects imperial to metric pipe.
- Reusable over and over again.
- No cleaning, drying or gluing needed.
- Ease of installation with stainless steel jubilee clip.
- Easy to fit and do it yourself. No more mistakes!
- Simple to fit, connect and tighten.
- Gives the perfect seal, no more leaks!
- Easy to apply in tight spaces due to flexibility.



## EPDM RUBBER

### MANUFACTURED IN EPDM, (ETHYLENE PROPYLENE DIENE MONOMER (M CLASS)) RUBBER

- EPDM combines excellent resistance to deterioration due to the effects of ozone, oxygen, weather, heat and many chemicals.
- Its serviceable temperature range is -40°F to +250°F and intermittent to +275°F.
- It is not recommended for use in contact with petroleum oils or fluids
- Hardness tolerance for a nominal IRHD value of 60 is  $\pm 5$
- Tensile strength at least: 9 MPa
- Elongation at break %: >300
- Ageing for 7 days at 70°C the material must still be within the following property ranges;
  - Hardness change max/min: +8/-5
  - Tensile strength drop as a percentage: -20%
  - Elongation change as a percentage: +10%/ -30%
- Stress Relaxation maximum reduction in % - 7 days @70°:  
<15% relaxation of tensile stress - 100 days @23°C:  
<22% relaxation of tensile stress
- Water Absorption - Volume change in water -  
Test for 7 days immersion @ 70°C note volume change:  
Acceptable range is from -1% up to +8% net change in volume



## STRAIGHT CONNECTOR

### Available in a range of sizes

- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P01-34	34mm	1 ¼"
0635P01-40	40mm	1 ½"
0635P01-54	54mm	2"



## 90° BEND

### Available in a range of sizes

- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P02-34	34mm	1 ¼"
0635P02-40	40mm	1 ½"
0635P02-54	54mm	2"



## TEE PIECE

### Available in a range of sizes

- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P03-34	34mm	1 ¼"
0635P03-40	40mm	1 ½"
0635P03-54	54mm	2"



## RUNNING TRAP

### Available in a range of sizes

- Add to plumbing run at the source of the problem
- Simply squeeze the running trap to clear blockages and save money!
- Stop bad odours
- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P04-34	34mm	1 ¼"
0635P04-40	40mm	1 ½"
0635P04-54	54mm	2"



## ADAPTOR

### Available in a range of sizes

- Compatible with all Imperial and Metric Sizes
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P05-34/40	34/40mm	1 ¼" 1 ½"
0635P05-34/54	34/54mm	1 ¼" 2"
0635P05-40/54	40/54mm	1 ½" 2"



## P TRAP

### Available in a range of sizes

- Installed underneath the sink
- Simply squeeze to clear blockages and save money!
- Stops bad odours
- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P06-34	34mm	1 ¼"
0635P06-40	40mm	1 ½"
0635P06-54	54mm	2"



## SAMPLING POINT

### Tee Reducer and Drain Valve

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
1905P05	54mm	2"



## BOSS 50MM

### Pipe Fitting Reducer

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P07	110/50mm	4" / 2"



## BOSS 34/40MM

### Pipe Fitting Reducer

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P08	110/32/42mm	4" / 1 1/4" / 1 1/2"



## ENDCAP

### Available in a range of sizes

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P10-34	34mm	1 1/4 "
0635P10-40	40mm	1 1/2 "
0635P10-54	54mm	2"



## FLEXIBLE HOSE

### Available in a range of sizes

- Increases flexibility for installation
- Increases mobility for GreaseShield, Integrated Work Station etc
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0604P19-1.5	40mm	1 1/2 "
0604P19-2.0	54mm	2"



## 45° BEND

### Available in a range of sizes

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P12-34	34mm	1 1/4 "
0635P12-40	40mm	1 1/2 "
0635P12-54	54mm	2"



## SEWER FIXING BRACKET

### Fixed pipes or fittings

- Material - Copolymer-Polypropylene • Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0604P38-A-54	54mm	2"



# FLEXIPLUMB™

## KEY BENEFITS

- Ease of installation with stainless steel jubilee clip
- Easy to fit and do it yourself
- Highly flexible allowing for misalignment
- Freedom from corrosion

## KEY APPLICATIONS

- Commercial Kitchens
- Hotels
- Domestic Applications etc.



# PLUMBERS MATE

Simple alignment and fixing tool for 32mm, 40mm and 50mm pipe or Imperial equivalent.

Correct invert drainage levels every time!!.



**Contact EPAS for your copper and plastic plumbing fitting needs.**

Contact: [Sales@FlexiPlumb.eu](mailto:Sales@FlexiPlumb.eu) for more details  
**Or Visit [FlexiPlumb.eu](http://FlexiPlumb.eu) for FULL Product Range**